

Item description/product images

**Description****Material:**

T-grip made from reinforced thermoplastic
Bush or threaded pin steel.

Version:

Grip graphite black RAL 9011.
Steel blue passivated.

Note:

Slight colour deviations or a marbled surface are possible due to the materials used and production process, but do not constitute a defect.

Application:

Sensitive electrical or electronic equipment, components and devices (ESD sensitive elements) may be damaged or destroyed by electrostatic discharges (ESD) in the immediate vicinity.

Electrostatic discharges can come from people or through handling ESD sensitive components (e.g. during production, assembly, transport, storage etc).

Electrically conductive products which conform to DIN EN 61340-5-1 are essential within electronic environments to prevent an electrostatic discharge.

These products can be used for ESD applications or in ESD protection areas (EPA) in accordance with DIN EN 61340-5-1.

Safety:

These ESD products can also be used for devices, components and protection systems in areas with high risk of explosion.

Use of these ESD products prevents the occurrence of electrostatic spark discharges, eliminating the potential ignition of gases and dusts which could lead to explosions in enclosed spaces.


Manufacturers and operators must use and conform to ATEX directives for the protection of persons working in areas with high risk of explosion.

Target groups:

Device manufacturers required to conform to ATEX product directive 2014/34/EU.

Operators required to conform to ATEX worker protection directive 1999/92/EC.

Drawings



Overview of items

Order No.	Form	A	B	D	D3	H	H1	L
06648-08-5505X15	L	55	12,6	M5	16	33	21,3	15
06648-08-5505X20	L	55	12,6	M5	16	33	21,3	20
06648-08-6506X20	L	65	14,6	M6	18	37	22,9	20
06648-08-6506X25	L	65	14,6	M6	18	37	22,9	25
06648-08-6506X30	L	65	14,6	M6	18	37	22,9	30
06648-08-6506X40	L	65	14,6	M6	18	37	22,9	40
06648-08-6508X20	L	65	14,6	M8	18	37	22,9	20
06648-08-6508X25	L	65	14,6	M8	18	37	22,9	25
06648-08-6508X30	L	65	14,6	M8	18	37	22,9	30
06648-08-6508X40	L	65	14,6	M8	18	37	22,9	40
06648-08-7508X20	L	75	18,4	M8	22	41	25,2	20
06648-08-7508X25	L	75	18,4	M8	22	41	25,2	25
06648-08-7508X30	L	75	18,4	M8	22	41	25,2	30
06648-08-7508X40	L	75	18,4	M8	22	41	25,2	40
06648-08-7510X20	L	75	18,4	M10	22	41	25,2	20

Overview of items

Order No.	Form	A	B	D	D3	H	H1	L
06648-08-7510X30	L	75	18,4	M10	22	41	25,2	30
06648-08-7510X40	L	75	18,4	M10	22	41	25,2	40
06648-08-7510X50	L	75	18,4	M10	22	41	25,2	50
06648-08-8510X30	L	85	19,6	M10	24	45	26,5	30
06648-08-8510X40	L	85	19,6	M10	24	45	26,5	40
06648-08-8510X50	L	85	19,6	M10	24	45	26,5	50
06648-08-8512X30	L	85	19,6	M12	24	45	26,5	30
06648-08-8512X40	L	85	19,6	M12	24	45	26,5	40
06648-08-8512X50	L	85	19,6	M12	24	45	26,5	50