

Item description/product images



Side mounted in profile keyway

no drilling required when using a T-slot nut



Profile end mounted



Description

Material:
Body fibreglass reinforced thermoplastic.
Spindle and washer steel.


Version:
Body black.
Spindle and washer galvanised.

Note:
These machine feet are suitable for tables and lighter installations. The foot height is adjusted by turning the base nut by hand or spanner. The pins on the top flange centre the foot and prevent it turning. These levelling feet can be attached to aluminium profiles using T-slot nuts, no need for drilling.

On request:
ESD antistatic.
Other colours.

Drawing reference:
1) support flange
2) nut

Drawings



Overview of items

Order No.	A for aluminium profile	B	C for slot	D	D1	D2 for countersunk screw	H	H1	L	SW1	Load rating max. kN (static load only)
27840-300606	30	20,5	6	30	M6	M4	35-50	44-59	9	22	1,5
27840-300806	30	20,5	8	30	M6	M4	35-50	44-59	9	22	1,5
27840-300808	30	20,5	8	30	M8	M4	35-50	44-59	9	22	1,5
27840-350808	35	20,5	8	35	M8	M4	35-50	44-59	9	22	1,5
27840-400808	40	28	8	40	M8	M6	45-65	54-74	9	30	1,5
27840-401006	40	28	10	40	M6	M6	45-65	54-74	9	30	1,5
27840-401008	40	28	10	40	M8	M6	45-65	54-74	9	30	1,5
27840-450808	45	28	8	45	M8	M6	45-65	54-74	9	30	1,5
27840-451008	45	28	10	45	M8	M6	45-65	54-74	9	30	1,5
27840-501008	50	28	10	50	M8	M6	45-65	54-74	9	30	1,5