

商品概述

家族编号	摘要 部分 (T) 全部 (V) 关于 (Ü)	每对最大 负载能力, 单 位 kg	轨道长度, 单位 mm (缩回)	材质 钢制 (S) 不锈钢 (ES) 铝制 (A)	水平安装	钢制安装 支架	Soft- Close	Push to open	自行回 拉	打开定 位器	关闭定 位器	前侧快速 分离
21332-05	V	4	80 - 150	A	N							
21332-15	T	7	70 - 150	A	N							
21332-40	Ü	12	80 - 150	ES	N							
21333-90	V	15	150 - 400	ES	X							
21333-95	T	18	80 - 150	ES	N							
21334-70	T	20	200 - 500	S	X							X
21334	V	20	150 - 500	S	N							
21334-03	V	30	200 - 600	S	N							
21334-05	T	35	305 - 711	S	N					X		
21334-10	V	45	150 - 550	S	N							
21334-25	T	50	300 - 700	S	X	21335-81				X	X	
21334-30	T	50	250 - 700	S	N	21335-80					X	X
21334-30	T	50	250 - 700	S	N	21335-80				X	X	X
21334-20	T	50	305 - 711	S	X							
21334-15	V	45	300 - 700	S	N	21335-80		X	X		X	X
21334-15	V	45	350 - 700	S	N	21335-80	X				X	X
21334-15	V	50	300 - 700	S	N	21335-80		X	X		X	X
21334-15	V	50	250 - 700	S	N	21335-80				X	X	X
21334-15	V	50	150 - 700	S	N	21335-80					X	X
21334-15	V	50	300 - 650	S	N	21335-80			X		X	X
21334-15	V	50	300 - 650	S	N	21335-80			X		X	X
21334-35	Ü	55	350 - 700	S	N	21335-80					X	
21334-40	Ü	60	300 - 700	S	N						X	X
21334-45	T	65	305 - 711	S	X					X		X
21334-50	T	65	300 - 700	ES	X						X	
21334-53	V	68	250 - 700	S	N	21335-85					X	X
21334-54	V	68	300 - 700	S	X				X		X	X
21334-63	Ü	68	305 - 711	S	X					X	X	X
21334-55	Ü	68	305 - 711	S	X					X		X
21334-60	Ü	68	305 - 711	S	X						X	X
21334-65	Ü	68	305 - 711	S	X	21335-83					X	
21334-70	Ü	70	305 - 711	S	X	21335-83						
21334-75	Ü	70	305 - 711	S	X	21335-83				X		X
21334-80	Ü	70	305 - 711	ES	X					X		X
21334-85	V	80	300 - 700	ES	X						X	
21334-86	V	80	300 - 700	ES	X	21335-85						
21334-90	Ü	82	406 - 762	S	X	21335-83				X		X
21334-91	V	90	300 - 790	S	X	21335-82	X		X			X
21334-93	V	90	400 - 790	ES	N	21335-85	X		X			X
21334-94	Ü	90	300 - 790	ES	N							X
21334-95	Ü	90	305 - 660	ES	X					X		X

商品概述

家族编号	摘要 部分 (T) 全部 (V) 关于 (Ü)	每对最大 负载能力, 单 位 kg	轨道长度, 单位 mm (缩回)	材质 钢制 (S) 不锈钢 (ES) 铝制 (A)	水平安装	钢制安装 支架	Soft- Close	Push to open	自行回 拉	打开定 位器	关闭定 位器	前侧快速 分离
21335	V	100	400 - 700	S	X		X				X	
21335-01	V	100	400 - 790	ES	N	21335-85	X		X			
21335-05	Ü	100	300 - 700	S	X		X				X	
21335-06	Ü	100	400 - 790	S	X							
21335-07	V	120	300 - 1100	S	N	21335-82				X	X	
21335-10	V	124	305 - 711	S	N	21335-83					X	X
21335-15	V	160	305 - 914	S	X	21335-81					X	X
21335-20	Ü	160	300 - 1100	S	N	21335-82 21335-83					X	
21335-23	V	270	400 - 100	A	N							
21335-25	V	272	305 - 1524	S	N					X	X	
21335-30	V	272	254 - 1524	S	X	21335-81						
21335-35	V	300	300 - 1000	A	N							
21335-70	V	622	500 - 1600	S	X							
21335-75	V	980	500 - 2000	S/ES	X							
21336	V	305	210 - 930	S	X							
21337-10	V	420	300 - 1200	S	N							
21342	V	459	290 - 1490	S	N							
21337-15	V	480	400 - 1500	S	N							
21340	T	741	290 - 610	S	N							